





# Super-Flex® 6-part body wire rope slings

## 615 SIX-PART FLAT BRAIDED SLING

	Rope Dia. (in.)	Width of Body	Thickness of Body	RATED CAPACITY - Tons*			Eye Dimensions		Slip Thru Thimble	Heavy Thimble
				Vertical	Choker Hitch**	Basket Hitch	A	B		
										
<b>XIP® IWRC</b>	#3/32	7/16	1/4	0.42	0.37	0.84	2	4	W-2	1/4
	#1/8	9/16	3/8	0.84	0.74	1.7	3	6	W-2	5/16
	3/16	13/16	1/2	1.6	1.4	3.2	4	8	W-3	1/2
	1/4	1-1/8	11/16	2.9	2.5	5.7	5	10	W-4	5/8
	5/16	1-3/8	7/8	4.4	3.9	8.9	6	12	W-4	3/4
	3/8	1-11/16	1	6.3	5.5	13	7	14	W-5	7/8
	7/16	2	1-3/16	8.6	7.5	17	8	16	W-5	1
	1/2	2-1/4	1-5/16	11	9.8	22	9	18	W-6	1-1/8
	9/16	2-1/2	1-1/2	14	12	28	10	20	W-6	1-3/8
	5/8	2-13/16	1-11/16	17	15	35	11	22	W-7	1-1/2
	3/4	3-3/8	2	25	22	49	12	24	W-8	1-5/8
	7/8	4	2-5/16	33	29	67	14	28	W-9	2
	1	4-1/2	2-11/16	43	38	87	16	32	W-10	-



# Made with 7x19 GAC component rope.  
 \* Rated Capacities Basket Hitch based on D/d ratio of 25 times the component rope diameter.  
 \*\* See Choker Hitch Rated Capacity Adjustment on Page 5.  
 Rated Capacities based on pin diameter no larger than natural eye width or less than the nominal sling diameter.  
 Rated Capacities based on design factor of 5.  
 Horizontal sling angles less than 30° shall not be used.  
 All capacities in tons of 2,000 lbs. All eye and fitting dimensions in inches.



Form No. 2040